

Permeaflon® M10W

Venting Membrane



Reliable protection against pressure variations and water ingress

In the interior of hermetic housings, in containers, headlights or batteries, changes in temperature or differences in height cause substantial variations in internal pressure.

Permeaflon® pressure compensation units (PCUs) from Berghof compensate for differences in pressure and prevent penetration by water, dust, grime and even oils. The pressure compensation units therefore guarantee the reliable functioning of components throughout their long life cycle.

Physical and Technical Specifications | Membrane

Reference thickness	0.5 mm
Material	Permeaflon® Polytetrafluorethylene (PTFE); porous, isostatically pressed, sintered Hydrophobic Oleophobic acc. to AATCC 118 / ISO 14419 (optional) Free of PFOA and PFOS
Colour	White / natural
IP protection class @RT; test area 1 cm ²	IP67 (≥ 100 mbar; 30 min)
Typical water entry pressure @RT; test area 1 cm ²	≥ 100 mbar
Typical airflow rate @RT; Δp = 70 mbar (1.0 psi)	≥ 85 L/(h·cm ²)
Chemical resistance	Virtually universal
Thermal resistance	-200 to +250 °C
Flammability	UL 94 V-0
Physiological properties	Physiologically insignificant At temperatures of > 400 °C gaseous by-products from thermal decomposition which are harmful to health must be reckoned with.
Storage	May be stored indefinitely at room temperature.
Processing information	No predefined direction of installation. Can be welded to various plastics by thermal and ultrasonic means. Weldability should be tested in each instance.

Physical and Technical Specifications | Membrane

<p>Conformity</p>	<p>Substances of Very High Concern (SVHC) (REACH). Directive 2011/65/EU on restricting the use of certain hazardous substances in electrical and electronic equipment (RoHS2). Perfluorooctanesulfonates (PFOS) as identified in EU Directive 2006/122/EC (30th amendment to EU Directive 76/769/EEC) or Perfluorooctanoic acid (PFOA), its salts and related compounds as described in (EU) 2019/1021 (POP).</p>
<p>Supplied as</p>	<p>Tape Stamped parts Our highly qualified staff will be pleased to help you in developing user-specific ventilation and extraction solutions. Please contact us with your requirements.</p>

Note: Guide values are given in this data print-out that have been compiled on the basis of current experience and knowledge. These values may be influenced by processing conditions, modifications, additives and environmental conditions and do not release users from the obligation to carry out their own checks and trials. A legally binding guarantee of particular properties or suitability for a concrete purpose cannot be derived from our information.